

Soy Seal[®] XD 6.0 pcf B – Component Material Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name:	BioBased [®] Soy Seal [®] XD 6.0 pcf B – Component
Synonyms/Generic Names:	Polyol blend with Amine Catalyst
Product Use:	Polyurethane resin system
Manufacturer:	BioBased Technologies [®] LLC 1200 Stewart Place, Springdale, AR 72764. (479) 966-4600 (479) 966-4601 (fax) Website: <u>www.biobased.net</u>
In Case Of Emergency	CHEMTREC (800) 424-9300 (24 Hours/Day, 7 Days/Week, US and Canada)
Call:	or call (collect) at (703) 527-3887 (USA)

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: An opaque liquid with a slight ammonia-like odor. Liquid and mists can burn the skin, the eyes and respiratory tract. Liquid and vapor is harmful via skin contact, inhalation or ingestion. Liquid or vapors may cause allergic skin or respiratory reactions to individuals sensitive to amines.

OSHA Hazard Communication Standard:	This product is considered hazardous.

Potential Health Hazards:

Skin:	Can irritate the skin. Can be absorbed through the skin and large or repeated exposures may result in toxic effects similar to ingestions. Can cause allergic skin reactions in individuals sensitized to amines. Skin exposure may trigger an allergic respiratory response.
Eyes:	Can cause irritation and/or burns and untreated exposures may result in blindness.
Inhalation:	Vapors and mists may cause irritation to respiratory tract with possible burns to throat and airways. Vapors can irritate or burn the eyes. Can cause severe allergic reactions in individuals sensitized to amines. Inhalation of large quantities may result in symptoms similar to ingestion.
Ingestion:	Harmful if swallowed. Can irritate or burn the digestive tract. If vomited, may enter lungs, causing lung damage.
Delayed Effects:	Repeated exposure in the absence of recommended protective clothing and without following recommended safe handling practices may cause individuals to become sensitized to amines.

Ingredients found on one of the three OSHA designated carcinogen lists are listed below.

Ingredient Name	NTP Status	IARC Status	OSHA List
No ingredients listed in this section.			

MSDS: Soy Seal® XD 6.0 pcf B Current Issue Date: Jan 28, 2011 Page 1 of 7

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient Name	CAS Number	Weight %
Hydroxylated Soybean Oil	693217-63-9	< 40
Bis (2-dimethyaminoethyl)ether	3033-62-3	< 1
Additive 1 (polyol compound)	Trade Secret	< 40
Additive 2 (diamine compound)	Trade Secret	< 10
Blowing agent (Not hazardous)	Trade Secret	< 10

Trace impurities and additional material names not listed above may appear in Section 15 of this MSDS. These materials may be listed for local "Right-To-Know" compliance and for other reasons.

4. FIRST AID MEASURES

Skin:	Immediately rinse under running water while removing contaminated clothing. Continue washing for up to 15 minutes. Get medical assistance for irritation. Launder contaminated clothing before reuse and discard any contaminated leather apparel (shoes, watch band, etc.)
Eyes:	Immediately flush eyes with running water while lifting the eyelids and continue for up to 15 minutes. Lift eyelids to wash out any liquid. Get immediate medical attention.
Inhalation:	Move the exposed person to fresh air. If person has difficulty breathing or is in distress, immediately contact a doctor, poison control center or paramedic. Provide oxygen if a trained responder is available. For irritation, burns or any systemic (internal) symptom, get immediate medical assistance.
Ingestion:	Immediately consult a physician or poison control center. Do not induce vomiting. If conscious and not nauseous, patient may drink one or two glasses of water or milk.
Advice to Physician:	Product is corrosive to skin and eyes and contains traces of respiratory and dermal sensitizers (amines). For sever cases of respiratory sensitization, anaphylactic shock is possible. For other respiratory exposures, monitor patient for any delayed respiratory involvement (e.g., pulmonary edema). No specific antidote is recommended. Treat symptomatically.

5. FIRE FIGHTING MEASURES

Flammable Properties

Flash Point (and method)	> 210 °F (99 °C) Pensky Martin Closed Cup
Autoignition Temperature:	Not determined
Upper Flame Limit (volume % in air):	Not determined
Lower Flame Limit (volume % in air):	Not determined
Flame Propagation Rate (solids):	Not applicable
OSHA Flammability Class: (storage)	Not applicable.

MSDS: Soy Seal® XD 6.0 pcf B

Extinguishing Media:	Water fog, high expansion foam, dry chemical, carbon dioxide or water spray. Avoid solid stream of water if liquid is heated to ignition. It may spread burning liquid.
Unusual Fire And Explosion Hazards: Sealed containers can rupture violently when exposed to fire.	
Special Fire Fighting	Wear self contained breathing apparatus. Avoid skin or eye
Precautions/Instructions:	contact with liquid and vapors.

6. ACCIDENTAL RELEASE MEASURES

In Case Of Spill or Other Release:	(See Section 8 for recommended personal protective equipment.) Avoid contact with skin and eyes. Do not breathe product vapors.
	Small spills: Soak up with absorbent material such as oil-dry or vermiculite. Shovel into containers but DO NOT seal them. Arrange for disposal.
	Large spills: Ventilate area during cleanup. Dike spill and pump into suitable containers for disposal. Do not allow to enter natural waterways or sewers.

Spills and releases may have to be reported to Federal and/or local authorities. See Section 15 regarding reporting requirements.

7. HANDLING AND STORAGE

Normal Handling:	Avoid contact with skin, eyes and clothing. Do not breathe product vapors or mists. (See Section 8 for recommended personal protective equipment.)
Storage	Keep containers closed during storage. Store away from moisture, isocyanates and
Recommendations:	oxidizing agents. (See Section 10 for hazards associated with contamination.)
	Do not contaminate with any material. Contamination with isocyanates or BioBased A - Component may cause a reaction generating pressure that could cause a closed container to explode.
	Product life is approximately 6 months when stored between 60 & 90 °F (16 & 32 °C).
	Do not allow product to become contaminated with other materials, especially with
	BioBased® A - Component or any isocyanate.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:	Provide local exhaust ventilation sufficient to keep vapors below safe exposure
	limits.

Personal Protective Equipment

Skin Protection:	Wear impervious gloves and clothing are recommended. Suitable materials of construction for gloves include butyl rubber, nitrile rubber, polyvinyl alcohol, PE/EVAL or PV/EVCH (4H TM and Silver Shield TM brand gloves). Tychem BR, LV or TK protective clothing may be appropriate. Butyl rubber, nitrile rubber neoprene and Saranex coated Tyvek may also be considered for use. Use of rubber footwear or overshoes is recommended.
Protection:	Wear safety glasses with eye-shields or chemical safety goggles. Avoid the use of contact lenses for liquid transfer and handling operation.
Respiratory Protection:	Not required for properly ventilated areas. For areas containing product mists, for areas where the exposure limits may be exceeded and for spill cleanup, use an

MSDS: Soy Seal® XD 6.0 pcf B Current Issue Date: Jan 28, 2011 Page 3 of 7

	air supplied respirator.	
Additional	A source of running water such as a safety shower and/or eyewash station is	
Recommendations:	recommended in the work area.	

Exposure Guidelines

Ingredient	ACGIH TLV	OSHA PEL	Other Limit
Bis(2-dimethylaminoethyl) ether	0.05 ppm TLV (skin)	None established	None established
	0.15 ppm STEL		

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Opaque liquid		
Physical State:	Liquid		
Odor	Slight ammonia odor		
Specific Gravity (water = 1.0):	1.12 (bulk density is 8.43 lbs/gallon)		
Solubility In Water (weight %):	Not determined		
pH:	Not determined		
Boiling Point:	Not determined		
Freezing Point:	Not determined		
Viscosity	Not determined		
Vapor Pressure:	Not determined		
Vapor Density (air = 1.0):	Not determined		
Evaporation Rate:	Not determined Compared To:		
% Volatiles:	Not determined		
Flash Point: (and method)	> 210 °F (99 °C) Pensky Martin Closed Cup		
Autoignition Temperature:	Not determined		
Upper Flame Limit (volume % in air):	Not determined		
Lower Flame Limit (volume % in air):	Not determined		

10. STABILITY AND REACTIVITY

Normally Stable:	Stable under normal storage conditions.	
Incompatibilities:	Do not contaminate with any material. Contamination with isocyanates or BioBased® A - Component may cause a reaction generating pressure that could cause a closed container to explode. Product may also react violently with oxidizing agents and acids.	
Hazardous Decomposition Products:	Carbon monoxide, carbon dioxide, nitrogen oxides and organic residues	
Hazardous Polymerization:	Can occur as a result of contact with polyisocyanates. Uncontrolled mixture with BioBased® A - Component may result in a violent reaction. – Always follow product use instructions.	

MSDS: Soy Seal® XD 6.0 pcf B

^{1 =} Limit established by BioBased Insulation[®].
2 = Workplace Environmental Exposure Level (AIHA).
3 = Biological Exposure Index (ACGIH).

11. TOXICOLOGICAL INFORMATION

Acute Toxicity:	This product has not been tested as a mixture.	
Eye Irritation:	Considered corrosive to the eyes based on ingredient information.	
Skin Irritation:	Considered corrosive.	
	Skin contact can trigger respiratory sensitization responses.	
Respiratory Contact	Considered an irritant and corrosive. May cause sever respiratory allergic	
	reaction in individuals sensitized to amines.	
Chronic data:	Permanent sensitization of the skin and respiratory tract can occur from	
	repeated exposures. (Allergic reaction whenever exposure occurs.)	

12. ECOLOGICAL INFORMATION

No data available on product. Avoid contact with natural waterways and soils.

13. DISPOSAL CONSIDERATIONS

RCRA

Is the unused product a RCRA hazardous waste if discarded?	No
If yes, the RCRA ID number is:	

The information offered in Section 13 is for the product as shipped. Use and/or alterations to the product such as mixing with other materials may significantly change the characteristics of the material and alter the RCRA classification and the proper disposal method.

Other Disposal	Liquid product should be incinerated in a licensed facility in accordance with local, state	
Considerations:	and federal regulations. Do not discharge to waterways or sewer systems or dispose of	
	on the ground.	
	Under no circumstances should a torch, welder, plasma cutter or similar tool	
	capable of producing an arc be used on an empty container regardless of the	
	whether the container has been rinsed or cleaned. Containers should be punctured	
	with a non-sparking tool and disposed of in a licensed facility or landfill.	

14. TRANSPORT INFORMATION

Shipping Name:	Resin Compound
UN ID Number"	Not applicable
Packing Group	Not applicable
US DOT Hazard Class:	Not regulated
Canadian TDG Hazard	Not regulated
Class:	
IMDG Hazard Class (sea):	Not regulated
IATA Hazard Class (air):	Not regulated

MSDS: Soy Seal® XD 6.0 pcf B Current Issue Date: Jan 28, 2011 Page 5 of 7

15. REGULATORY INFORMATION

Toxic Substances Control Act (TSCA)

TSCA Inventory Status:	Listed on TSCA Chemical Inventory	
Other TSCA Issues:	None	

SARA Title III/CERCLA

"Reportable Quantities" (RQs) and/or "Threshold Planning Quantities" (TPQs) exist for the following ingredients.

Ingredient	SARA/CERCLA RQ (lb)	SARA EHS TPQ (lb)
No ingredients listed in this section.		

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center [(800) 424-8802] and to your Local Emergency Planning Committee.

SARA 311 Hazard Class: Immediate, Delayed

SARA 313 Toxic Chemicals:

The following ingredients are SARA 313 "Toxic Chemicals" and may be subject to annual reporting requirements. CAS numbers and weight percents are found in Section 2.

Ingredient	Comment
No ingredients listed in this section.	

State Right-To-Know

In addition to the ingredients found in Section 2, the following are listed for state right-to-know purposes.

Ingredient	Weight %	Comment
Formaldehyde (trace impurity)	< 30 ppm	California Proposition 65 Carcinogen

Additional Regulatory Information: None

Non-US Regulatory Information.

WHMIS Classification:	D2A This product has been classified in accordance with hazard criteria of the		
(Canada)	Controlled Products Regulations and the MSDS contains all the information		
	required by the Controlled Products Regulations.		
Other Chemical	Some ingredients not confirmed on Canadian DSL.		
Inventory Status:			

16.OTHER INFORMATION

Current Issue Date:	January 28, 2011
Previous Issue Date:	September 10, 2010
Changes from previous Issue Date:	Address change
Other Product Information:	None

MSDS: Soy Seal® XD 6.0 pcf B Current Issue Date: Jan 28, 2011 Page 6 of 7

Hazard Ratings

HMIS (III)	NFPA
Health – 3	Health – 3
Flammability – 1	Flammability – 1
Physical Hazard – 1	Instability – 1

The technical data contained herein is true and accurate to the best of BioBased Technologies LLC knowledge on the date of publication. The technical data is subject to change, however, and the user should contact BioBased Technologies LLC to verify that the technical data is current. In addition, the technical data is provided for your guidance only. Because many factors can affect the processing or application of the product and/or its use, it is the user's responsibility to test the product to determine its suitability for the user's intended use. The sale and use of this product is subject to all of the terms and conditions set forth in the BioBased Technologies LLC sales order, including the LIMITED WARRANTY, DISCLAIMER OF WARRANTY AND RELEASE, and EXCLUSION OF CONSEQUENTIAL AND OTHER DAMAGES. This technical data does not create an express warranty of any kind. The only warranty applicable to this product is the written, limited express warranty contained in the BioBased Technologies LLC sales order, which is extended to the purchaser only.